

Principal Particulars

Year Of Built	2009
Туре	AHTS
Flag:	тво
Offshore support vessel	AH, E, + AMS, + DPS 2
Class	ABS + A1,Towing vessel,Fi-Ff1
IMO No:	TBD
Length overall	59.78 m
Breadth moulded	15.00 m
Depth	5.50 m
Design draft	4.30 m
Bollard pull	82.5 t
Gross tonnage	1,733
Max draft	4.88 m
Deadweight (at max draft	t) 1,460 t

Capacities

Deck area: (5mt/m2).	(26,00 x 12,70 m) 331 m2
Deck cargo	540 mt
Fuel oil	606 m3
Drill/water/ballast	458 m3
Fresh water	354 m3
Liquid mud (8 tanks)	651 m3
Dry bulk/cement	156 m3
Foam	14.5 m3

Machinery

Main Engine	3 x 1,825 kW
Main propulsion	3 x 1,685 kW Z Drive,fixed
	pitch variable speed
Bow thrusters	2 x 560 kW
Emergency /	180kw

Accommodation

Accommodations	for 20 pers
Single cabins	4
2 man cabins	4
4 man cabins	2
Mess / day rooms, hospital,	
laundry, galley, stores, office. Fully air	
conditonned.	

Speed / Consumption

Maximum speed (100 %)	22 t/day @13.5 knots
Service speed (%80)	16 t/day @12 knots
Economic speed (%50)	8.3 t/day @ 10 knots
Stand-by mode (1 genset)	5.4 t/day in moderate
	environnemental
	conditions.

Deck Equipment

Drum size	900/2.250 mm dia. x	
	1,800 mm length	
Drum capacity	1,500 m of 2" steel wire	
Rated pull	150 ton 1 st. Layer at	
	8.50 - 0 m /min	
Brake holding load	250 t on 1 st layer	
Cable lifters	2 for 2/1 ''2 and 3" chains	
Stern roller	1,500 mm dia. X 2,500 mm length	
Storage reel	2,300/813 mm dia. X 1,600 mm length	
Capacity	1,500 m of 2" wire	
Windlass	1	
Tugger winchs	2 x 10 t pull	
Deck cargo crane	1.8 t @ 6 m	
Towing /Anchor-handling electro-hydraulic		

high pressurewintch

Electronics

NAVIGATION / COMMUNICATION.

2 radars 1 radio system compliant with

GMDSS A3 .3 satellite communication

system: Vsat, Inmarst fleet 77, Iridium.

Email / IP voice facilities.

DYNAMIC POSITIONING SYSTEM (Class II)

ABS classed DP2 redundant

positioning system comprising

2 DGPS, 1 Cyscan

1 laser reference unit

1 independent joystick system

Sensors and monitoring as per class II requirements

DP Capability Plot



Current Speed - 0 Kts - 1 Kts - 2 Kts

Safety Equipment

Fire Fighting (Fi-Fi	2 pumps of 1,500 m3/h
Line pull	2 monitors of 1,200 m3/h
Water spray protection. MOB boat with davit Life	
saving arrangement Stand by rescue equipment	

Pumps

Fuel oil	150 m3/h at 60 m	
Fresh water	150 m3/h at 70 m	
Drill/ water/ballast	150 m3/h at 70 m	
Liquid mud	2 x 150 m3/h at 70 m	
Dry Bulk/Cement	50 t/h at 60 m	
Liquid mud tanks fitted with agitators and		
fixed washing system.		

AHTS, 6140 BHP, DP2