

VESSEL SPECIFICATIONS

5200BHP/BP70T/AHTS

• Flag: China

Home Port: Shanghai

Call Sign: T B DClassification: CCS

Builder: Shanghai Dongzhen Marine Engineering Co.,Ltd

Date of Delivery: October, 2009
Sailing Area: World-wide
Max speed: 13 knots
Accomodation: 33 person
Bollard pull: 70 tons

• Endurance: 7200 sea mile

DIMENSIONS

Length Overall: 63.4M
Length BP: 55.0M
Breadth Moulded: 14.0M
Depth Moulded: 6.60M
Draft: 5.10M

TONNAGE

Gross Tonnage: 1647 TonsNet Tonnage: 494 Tons

TANK CAPACITY

Diesel Tanks: 580 CUB.M
Cement Tanks: 200 CUB.M
Fresh Water Tanks: 400 CUB.M
Ballast Tanks: 425 CUB.M
Bulk Hold: 80 CUB.M

• Fuel Type: 0#

MACHINERY

• Main Engine: 6dkm-28

Horse Power: 1912kwX2sets, 750r/min, 195G/RAM FUEL/kw

• Propeller: CPC-80AF

• Main Generator: KC430GFM 400KW*2 380V 50HZ

Auxiliary Generator: 2xChongQingCummins,KTA19-D(M)/400KW

Emergency Generator: CCFJ90YCSt 90KW 380V 50HZ

• Thrusters: Bow: TT1650/MSB*CP 600KW 95KN

Stern: TT1300/MSB*CP 445KW 66KN

• Liquid Mud System: 40 cubic meter *2 SETS

Liquid Mud-air compressor: CYL132 0.75MPA

• Main air conpressor: HP7-35 3.5MPA

TOWING WINCH AND GEAR

● TYPE: HWTW-72/50*2 700/120KN 6/40M/MIN

The above specifications are provided in good faith but not guaranteed.

Towing wire: 52MM DIAMETER X 1000 M LENGTH
 Shifting cargo winch: 100KN*5M/MIN DIAMETER 22*200M

• Vertical hoist: HCAP-5 50KN

• SHARK JAW\TOWING PIN: HFTP-200/80

DECK EQUIPMENT

Deck Area: 400 Square M
Loading Capacity of Deck: 500 Tons

• Anchor and anchor chain: ANCHOR:3*2280KG, CHAIN:AM3-36*852.5M

Windlass: 36*10M/MIN 100*25*120
 Telescopic Hoist: YQ5/9 9M/5T(5.2M+3.8M)
 Rope Winch: 50KN 0-20/MIN 100*220M

• Fire fighting: 50cub/h x 50M

• Water gun: Output GP-1200,1800RPM 140M 700KW

NAVIGATION

• GYRO AND MAGNETIC COMPASS CONNECTED TO AUTOPILOTS AND

RADARS/GPS: STANDARD22

RADAR: FAR-2137*2
 DGPS: GP-150*2
 ECHO SOUNDER: FE-700

• WEATHER FACSIMILE: FAX-408

• AIS: FA-150

COMMUNICATION

• VHF RADIO: FM-8800S(DSC)*2

• MF/HF RADIO EQUIPMENT: RC-1800T

• INMARSAT-F: FELCOM-70

• SATELLITE EPIRB AND SART / NAVTEX RECEIVER: NX-700A

SALVAGE EQUIPMENT

• Cement and Brine Pump: E2H2650-Q-W102 48CUB.M/H 0.8MPA