

# 2x 900 HP Land Drilling Rigs

Rig 274 | Rig 721



## Rig #274

---

US \$550,000

### **DRAWWORKS:**

Franks Cabot 2342, with an input rating of 900 horsepower, Parmac V-80 hydromatic brake, crown o matic and Foster catheads, 1-1/8" drill line

### **PRIMARY POWER:**

Two Caterpillar C-13 engines rated at 500 HP each, equipped with two Allison CLBT 5860 power shift transmissions

### **MAST:**

Franks Cabot D350-117 telescoping, 117 ft. clear height x 15 ft. base at floor, API static hook load of 350,000 lbs. on 8 lines

### **SUBSTRUCTURE:**

Franks Cabot, telescoping, with 17 ft. floor height and 13 ft. clear height under the rotary beams – Substructure is designed for a 350,000 lbs. casing load simultaneous with a setback load of 200,000 lbs.

### **CARRIER:**

Franks Explorer III six axle carrier w/single man cab, rotary drive assembly, air/fuel/hydraulic tanks, drill line w/spool, braden hydraulic winch, folding walkways, 18 x 22.5 front & 11 x 24.5 rear tires w/budd wheels

### **MUD PUMPS:**

Two – National F 1000 mud Pumps with Caterpillar 3508 engines

### **HOOK/BLOCK:**

Gardner Denver - 200Ton

### **ROTARY:**

Mud King 17 1/2"

### **BLOW OUT PREVENTERS:**

11" 5M# Dbl Hydril B.O.P.

11" 3M# Annular Preventer (no outlets)

One 2" 5M# choke manifold with H2S Trim

### **MISC. EQUIPMENT:**

Automatic Driller

Wireline Unit

Full Opening Safety Valve

Vapor Proof Lighting System

Gas Buster

Poor Boy Degasser

Lower Kelly Valve

Two Hydraulic Hoist

0 – 7 Degree Drift Indicator

Inside B.O.P.

**NOTE: Rig #274**

Rig engine #1 - 18,364.6

Rig engine #2 - 16,077.50

Mud pump #1 - 10,799.00

Mud pump #2 - 30,248.02

## Rig #721

US \$750,000

### **DRAWWORKS:**

Franks Cabot 900Series, model 2342, with an input rating of 900 horsepower, Parmac V-80 hydromatic brake, crown o matic and Foster catheads, 1-1/8" drill line

### **PRIMARY POWER:**

Two Caterpillar C-13 engines rated at 500 HP each, equipped with two Allison CLBT 5860 power shift transmissions

### **MAST:**

Franks Cabot D350-117 telescoping, 117 ft. clear height x 15 ft. base at floor, API static hook load of 350,000 lbs. on 10 lines

### **SUBSTRUCTURE:**

Franks Cabot, telescoping, with 17 ft. floor height and 13 ft. clear height under the rotary beams – Substructure is designed for a 350,000 lbs. casing load simultaneous with a setback load of 200,000 lbs.

### **CARRIER:**

Franks Explorer III six axle carrier w/single man cab, rotary drive assembly, air/fuel/hydraulic tanks, drill line w/spool, braden hydraulic winch, folding walkways, 18 x 22.5 front & 11 x 24.5 rear tires w/budd wheels

### **MUD PUMPS:**

Two – National F-1000 horsepower mud pumps powered by D-398 caterpillar on each

### **MUD TANKS:**

800 Bbl system consisting of two 400 bbl tanks with a 50 Bbl slugging compartment in the suction tank, clean out gates, two centrifugal pumps for mud mixing (two 5" x 6" with a 60 H.P. motor), three 10 H.P. mud agitators.

#### **SOLIDS CONTROL:**

1,000 gpm capacity desander & one 800 gpm desilter  
Shale Shaker- Harrisburg D-235

#### **WATER STORAGE:**

One 350 Bbl tank

#### **FUEL STORAGE:**

One 7,770-gal tank (185 Bbl)

#### **HOOK/BLOCK:**

Gardner Denver - 300Ton

#### **SWIVEL:**

National Oilwell P-300

#### **ROTARY:**

Ideco 17 1/2"

#### **ACCUMULATOR:**

80 gallons, six station, with an electric triplex pump, one air operated pump, regulating valves and six station remote control

#### **BLOW OUT PREVENTERS:**

11" 5M# Dbl Hydraulic Shaffer B.O.P.  
11" 5M# Shaffer Annular Preventer (no outlets)  
One 3" to 2" 10M# choke manifold with H2S Trim

#### **MISC. EQUIPMENT:**

Automatic Driller  
Wireline Unit  
Full Opening Safety Valve  
Vapor Proof Lighting System  
Gas Buster  
Degasser  
Lower Kelly Valve  
One Hydraulic Hoist  
5-1/4" x 40' Square Kelly  
0 - 7 Degree Drift Indicator  
Inside B.O.P.  
Kelly Spinner Foster.

#### **NOTE: Rig #721**

Rig engine #1 - 20,051.90  
Rig engine #2 - 19,448.60  
Mud pump #1 cannot retrieve  
Mud pump #2 cannot retrieve

# GALLERY

---

