

Detergent 8.59mt **MACHINERY & PROPULSION SYSTEM** Main Engine 2 x 1800 bhp @ 1800rpm CUMMINS: KTA50M2 Bow Thruster 1 x 5T thrust engine driven VOLVO PENTA D12D-CMH Propeller 2 x Four blade Fixed Pitch in K/Nozzles 2 x 245kW @ 1500rpm Generator 6CTA8.3D(M), 415V/3 /50 **TOWING EQUIPMENT** Single Drum 50 tonnes Towing/ Winch Brake holding 120 tonnes. Drum capacity : 850m x 44mm dia SEKWANG SK-HTW-T050 **DECK EQUIPMENT** 2 x 1020 kg stockless bower anchors, 9 shackles 32mm Anchor diameter chains Anchor Windlass Electro-hydraulic powered. PLIMSOLL PC-HAW/GG-32 2 x 5t, PLIMSOLL PC-HVC-05/380 Capstan Tugger Winch 1 x 5m tons @ 15m/min PLIMSOLL PC-HUW-10/380 **ACCOMMODATION** All Cabins are fully air conditioned Cabins c/w attached 2 x 1 berth washroom 3 x 2 berth 3 x 4 berth (TOTAL 20 pax) **RADIO & NAVIGATION Communication Equipment** EQUIPMENT complied with A3 and Flag administration regulations. As per SOLAS & flag administration LIFE SAVING requirement **APPLIANCE & FIRE** FIGHTING CO2 System In engine room & bow thruster compartment 1x 6 persons NARWHAL SV-400 Rescue Boat External Fire Fighting

POLLUTION CONTROL

As per MARPOL





GENERAL Port of Registry/ Flag

GRT/ NRT

Year Delivered

PRINCIPAL PARTICULARS

Length Overall Length BP Breadth Moulded Depth Moulded Draft (Max) Class

PERFORMANCE

Bollard Pull (Certified)

Speed Economical Speed Type of Fuel Range

12 knots

Marine Gas Oil 5,500 nautical miles @ 10 knots

CARGO/TANK/LOADING

CAP. Deadweight Deck Cargo Deck Strength Clear Deck Area Fuel Oil Fresh Water


Foam

100% 344 tonnes 300m tons 5 tons/m² 150m² 332m³ 157m³ 8.59mt

45.00 mt (Static) 50.00 mt (Max.) 11 knots

(Approx)

½ FiĖi



Kuching, Malaysia