

Accommodation and Pipelay Barge for Shallow and Medium Water



The vessel is in warm lay-up at in Malaysia, and is inspectable by arrangement.

Built: 2012

Class: ABS

LOA: 137.25m

Breadth Moulded: 37.82m

Depth Moulded: 9m

Max Draft: 4.5m

Min Draft: 2.8m

GRT/NRT: 19750/5928

DWT: 10,367 MT

LDT: 11,580 MT

Clear Deck Area: 2500m²

Deck Loading: 12.5 MT/m²

Fuel Oil: 4797.57 MT

Ballast Water: 7248.4 MT

Potable Water: 1965.43 MT

Fresh Water: 4744.1 MT

Accommodation

Total: 300 personnel

10 x 1-man cabin

135 x 2-man cabin

4 x 4-man cabin

Sewage Treatment

Model: KDOceanClean 300 Vacuum

Maker: Ocean Clean (Germany)

Capacity: 300 personnel

Sewage Holding Tank: 1.8 m²

Pipelay Capacity: Max 60 INCH coated pipe

Tensioner Machine: 2 x 70 MT

A&R Winch Work Station: 1 x 182 MT

Beveling Stations: 4

Line-up Stations: 3

Automatic Welding Stations: 7

NDT & Repair Stations: 3

Field Joint Coating Stations: 2

Side Davits: 6 x 50 MT

Stinger

Type: Rigid

1st Section: Length: 42m, Weight: 142 metric ton

2nd Section: Length: 19m, Weight: 46 metric ton

Machines

Miller Big Blue Eco Pro: 2 x 500 amp

Lincoln Welding Machine: 13 x 500 amp

Miller Gold Star 402 Arc Welding: 6

Crane/Helipad/Storm Anchor

Mooring and Tow System: 8 x Hydraulic Mooring Winches

Line Pull: 125 MT @ 13m/min at 1st speed @ 1st layer

HOS offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A Buyer should instruct his agents, or his surveyors, to verify all details, as per Buyer desires (project/ scopes of work) in due course. This vessel is offered subject to availability, price change, or withdrawal without notice.