

Mobile Drilling Rigs

The mobile drilling rig range from 125 ton to 225 ton hookload capacity, is designed for conventional oilfield and geothermal drilling, workover and well-service applications. These rigs can be completed with a high number of options including rig automation, electric-drive and rig accessories.

	125	180	200	225
Rig Power	630HP (470kW)	1.080HP (794kW)	1.080HP (794kW)	1.260HP (940kW)
Theoretical Drilling Depth	2.400m (8.000ft) with 144mm (4½") DP	3.500m (11.500ft) with 144mm (4½'') DP	3.800m (12.450ft) with 144mm (4½") DP	4.200m (13.750ft) with 144mm (4½") DP
Theoretical Workover Depth	3.800m (12.500ft) with 89mm (3½") DP	4.600m (15.300ft) with 89mm (3½") DP	5.050m (16.800ft) with 89mm (3½") DP	5.600m (18.500ft) with 89mm (3½") DP
Maximum Hook Load	125Ton (275.000lbs)	180Ton (400.000lbs)	200Ton (440.000lbs)	225Ton (495.000lbs)
Mast Height	36m (118ft)	36m (118ft)	38m (124ft)	38m (124ft)
Substructure Height	5,20m (17ft)	5,20m (17ft)	6m (19,6ft)	6,70m (22ft)
Travelling System	5x4 (8 lines)	5x4 (8 lines)	6x5 (10 lines)	6x5 (10 lines)
Drill Line Dia.	26mm (1")	29mm (1")	32mm (1 ^{1/4} ")	32mm (1 ^{1/4} ")
Rotary Table Opening	698,5mm (27½")	698,5mm (27½")	698,5mm (27½")	698,5mm (27½")
Travelling & Hook Block Combo	160Ton (350.000lbs)	200Ton (440.000lbs)	200Ton (440.000lbs)	225Ton (495.000lbs)
Swivel Capacity	200Ton (440.000lbs)	200Ton (440.000lbs)	200Ton (440.000lbs)	225Ton (495.000lbs)
Deck Engine	630HP (470kW) Caterpillar C18 ACERT	2 x 540HP (403kW) Caterpillar C15 ACERT	2 x 540HP (403kW) Caterpillar C15 ACERT	2 x 630HP (470kW) Caterpillar C18 ACERT
Transmission	Allison S6620 Automatic	2 x Allison S5620 Automatic	2 x Allison S5620 Auto- matic	2 x Allison S6620 Auto- matic
Instrumentation	MD / Totco indicator & gauges,Rexroth pneumatic controllers	MD / Totco indicator & gauges, Rexroth pneumatic controllers	MD / Totco indicator & gauges,Rexroth neumatic controllers	MD / Totco indicator & gauges,Rexroth pneumatic controllers
Optional Top Drive	N/A	N/A	Compatible	Compatible